

Technical specifications	XT9050-A	XP9400-A	WE9700-A	PX1000-A
P/N	80X9050I10	80W9401I10	80W9700I10	80P1000I10
Processor/ Chipset	Intel Atom N270 1.6GHz / Intel 945GSE + ICH7-M			
Power supply	external 100/240VAC 50/60Hz, 12VDC / 4A max			
Power consumption: on / stand-by	13W / 1.95W standard version, 15W /1.95W with built-in wireless			
Device dim, weight / Packaging dim, weight	15,6(H) x 12,2(P) x 3,6(L) cm, 0,75 Kg / 22,1(H) x 23,2(P) x 8,5(L) cm, 1,520 Kg			
Device certifications / Power Supply certification	CE, FCC Class B, Energy Star 5.0 / CE, FCC Class B, GS TUV,UL			
Temperature range / humidity	0° ÷ 35° / 20% ÷ 80%			
Security lock	kensington			
Operating System	ThinOX V8	XP Embedded SP3	WES7 SP1	PXE Boot
RAM Memory / Flash memory	512MB / 512MB	1GB / 2GB	2GB / 4GB	512MB / --
Display res. with DDC, 4:3, 16:10 WIDE ratio	1920 x 1440			
Colors	from 256 to 16,8 Milion			
Peripherals				
USB ports / LAN Ethernet	4 USB 2.0 ports (2 front + 2 rear) / 10/100/1000 BaseT Ethernet RJ45			
Monitor	1 DVI-I port with DVI to VGA included			
PS/2 Mouse and keyboard	1 PS/2 port, PS/2 mouse and keyboard adapter included, optical mouse included			
Audio In MIC / Audio Out Headphones	1 x 1/8 inch jack / 1 x 1/8 inch jack			
802.11b/g/n built in wireless	Factory Option			
Built-in speaker	Built-in speaker 1 W			
Protocols and resident clients				
TCP/IP, DNS, DHCP, FTP, SNMP MIB II	•	•	•	--
802.1X Ethernet EAP/PEAP MSCHAPV	•	•	•	--
Cisco VPN Client	•	◇	◇	--
Client RDP	7.0	7.0	7.1	--
Client VMware View 5.0	RDP/PCoIP	RDP/PCoIP	RDP/PCoIP	--
Citrix ICA / PN Agent / Receiver	ICA 12	Receiver 3.0	Receiver 3.1	--
Virtual Bridges VERDE 5.5	SPICE	◇	◇	--
Ericom PowerTerm WebConnect Client	•	•	•	--
Leostream Client \ Provision Networks VAS	•	◇	◇	--
Browser	Firefox 3.0.1	IE 7.0	IE 8.0	--
Local PDF Viewer	Acrobat 7	Acrobat 7	◇	--
Microsoft .NET Framework		2.0	2.0-3.0-3.5	--
Media Player, Wordpad		•	•	--
E-mail client	Thunderbird 2.0	Outlook express		--
JVM	SUN 1.6	◇	◇	--
Flash Player	Adobe 11	◇	◇	--
Local voip Skype Client	•	◇	◇	--
NX Nomachine Client	•		◇	--
X11 nativo Client	•	◇		--
Propalms TSE Client	•	◇	◇	--
VNC Client	•		◇	--
Shell script sessions	•			--
CUPS printing support	•	•		--
LPD/LPR and RAW	•	•	•	--
User disk partition	50MB	~ 1GB	~ 1.5GB	--
Praim USB re-direction support	□	□	□	
Supported Operating Systems				
Citrix Metaframe 1.7, 1.8, XP, PS 4, 4.5	•	•	•	--
Citrix XenApp 6.0, XenDesktop 4.0, 5.0	•	•	•	--
Microsoft Windows 2000/2003/2008 TS	•	•	•	--
Unix/Linux/AIX, NX NoMachine Server	•	◇	◇	--
IBM AS/400, IBM S/390		Opt Net2000	Opt Net2000	--
Administration				
Remote management via Praim ThinMan	Freeware	Freeware	Freeware	--
FW upgrade / VNC shadowing / Wake On LAN	•	•	•	--
Screen saver with password	•	•	•	--
Options	P/N	P/N	P/N	P/N
External USB WiFi USB 802.11b/g dongle	80AC00031	80AC00031	80AC00031	80AC00031
Built-in wireless 802.11b/g	80AC00060	80AC00060	80AC00060	80AC00060
Built-in wireless 802.11b/g/n	80AC00063	80AC00063	80AC00063	80AC00063
Dual monitor optl cable adapter DVI-I to DVI/VGA	80EC00019	80EC00019	80EC00019	80EC00019
USB to Parallel cable adapter	80EC00012	80EC00012	80EC00012	80EC00012
Flash disk expansion	-	4GB	-	-
RAM memory DDR2 expansion	1GB, 2GB	2GB	-	1GB, 2GB
105 keys PS/2 PC keyboard	89T110001	89T110001	89T110001	89T110001
105 keys PS/2 PC/5250 keyboard	89T110002	89T110002	89T110002	89T110002
Praim Media streaming codecs Add-On	76AC00006	-	-	-
VESA mounting KIT	80EC00027	80EC00027	80EC00027	80EC00027
Warranty				
1 year ex-factory. Free 2 year warranty extension when the product is registered on the Praim web site				
Note:	• Available	◇ Installable from the user based on available free disk space	□ Requires ThinMan Enterprise Edition	
Praim Srl - info@praim.com - www.praim.com - T. +39 0461 420517 - F. +39 0461 420581 - Via Ezio Maccani 121, 38121 TRENTO - ITALY All names and trademarks contained in this document, are property of their respective owners. The information in this document is property of Praim SRL.				